


PTW Safety Checklist No. 70



USE OF AIR / HYDRAULIC POWERED EQUIPMENT

Other Checklists that may be relevant:		27 , 54 , 59
Permit Number:		Date:
Rev 2.1	Issue Date: 29/11/2022	Authorised By: PSM

CAUTION

- 1 The use of inline swivels attached to pneumatic tools are discouraged.
See item 4

PRIOR TO COMMENCING TASK:

	Y	N	N/A
2 All equipment, including hoses, has been checked thoroughly and all components are certified, in good condition and operating correctly.	<input type="checkbox"/>		
3 Ludecke couplings that are connected directly into a pneumatic tool, must be via an in-line straight swivel (360°).	<input type="checkbox"/>		<input type="checkbox"/>
4 Where a hose is connected directly into a pneumatic tool, it is done via a crimped dyna-swivel or similar universal joint.	<input type="checkbox"/>		<input type="checkbox"/>
5 Ensure all safety pins and whip checks are correctly attached across hose connections.	<input type="checkbox"/>		<input type="checkbox"/>
6 Are air operated tools fitted with the necessary lubricator / water separator to prevent freezing or other damage.	<input type="checkbox"/>		<input type="checkbox"/>
7 When using Magnetic base tools (e.g., a Rotabroach) on a vertical or overhead surface a safety chain must be connected to a solid structure.	<input type="checkbox"/>		<input type="checkbox"/>
8 Signs and barriers are in place to warn personnel of operations in area(s) as per Temporary Barriers and Barricades Standard Operating Procedure.pdf	<input type="checkbox"/>		<input type="checkbox"/>
9 The following additional PPE is to be worn when operating Hytorc equipment <ul style="list-style-type: none"> • Clear Face Shield. • Needlestick Level F gloves or Cut Level F Needle Handling gloves. 	<input type="checkbox"/>		<input type="checkbox"/>
10 Hytorc hoses from machine to tool must be fitted with Kevlar hose sleeves and secured with cable ties.	<input type="checkbox"/>		<input type="checkbox"/>