PTW Safety Checklist No. 89

NON CSE CELLAR ENTRY

SECTION 1



Υ

Ν

N/A

Other Checklists that may be relevant:		<u>35, 45, 47</u>
Permit Number:		Date:
Rev 3.0	Issue Date: 17/11/2020	Authorised By: PSM

THIS CHECKLIST ENABLES ENTRY INTO WELLHEAD CELLARS AS NON-CSE AS PER SECTION 1 DETAILS BELOW.

IF THE ANSWER TO ANY OF THE BELOW IS NO, DO NOT PROCEED WITH A NON CSE CELLAR ENTRY. INSTEAD PROCEED AS A CSE ACTIVITY WITH A CSE ENTRY PERMIT AND CHECKLIST 45

Access to cellar is via fixed platform or scaffold with a deck no deeper than 1500mm from lip of cellar. Work scope does not prevent entrant from freely standing with head above cellar lip at any time i.e.: not entangled in pipework etc. More than one form of ingress/egress must be available and <u>proven</u> prior to work commencing. A fixed ladder must be one of these (either permanent or temporary). Other possible methods may include but not limited to a portable step or temporary scaffold steps. Stipulate these ingress/egress methods and locations below:

4 Cellar entrants are to be kept at a <u>minimum</u>. Only the people required to perform the task shall enter the cellar. Note: The cellar size, layout and work activity will dictate the number required. Agreed number of entrants: (Max 2)

5	Gas test for oxygen, hydrogen sulfide, carbon monoxide and LEL carried out
	prior to entry and recorded

- 6 Entrant(s) has/have operational gas detector(s) on their person throughout entry.
- 7 During entry a person from the work party must remain outside the cellar to observe the activity within the cellar and surrounding wellsite This person does not need to be competent safety observer but must ensure the agreed controls for the cellar entry are being followed at all times.
- 8. All venting/de-pressuring to be vented to a safe area away from the cellar.

If the answer to any of the above is NO, stop and proceed with CSE entry permit and <u>Checklist</u> <u>45</u>.